

Operating Systems and Networks

Network Lecture 5: Network Layer 1

Adrian Perrig
Network Security Group
ETH Zürich


Pending Issues

- Exercise sessions are starting today!

2

Where we are in the Course

- Starting the Network Layer!
 - Builds on the link layer. Routers send packets over multiple networks



3

Why do we need a Network layer?


- We can already build networks with links and switches and send frames between hosts ...



4

Shortcomings of Switches


1. Don't scale to large networks
 - Blow up of routing table, broadcast



5

Shortcomings of Switches (2)


2. Don't work across more than one link layer technology
 - Hosts on Ethernet + 3G + 802.11 ...



6

Shortcomings of Switches (3)

- 3. Don't give much traffic control
 - Want to plan routes / bandwidth



7

Network Layer Approach

- **Scaling:**
 - Hierarchy, in the form of prefixes
- **Heterogeneity:**
 - IP for internetworking
- **Bandwidth Control:**
 - Lowest-cost routing
 - Later QOS (Quality of Service)

8

Topics


- Network service models
 - Datagrams (packets), virtual circuits
- IP (Internet Protocol)
 - Internetworking
 - Forwarding (Longest Matching Prefix)
 - Helpers: ARP and DHCP
 - Fragmentation and MTU discovery
 - Errors: ICMP (traceroute!)
- IPv6, the future of IP
- NAT, a "middlebox"
- Routing algorithms

This time
Next time

9

Routing vs. Forwarding


- **Routing** is the process of deciding in which direction to send traffic
 - Network wide (global) and expensive



10

Routing vs. Forwarding (2)

- **Forwarding** is the process of sending a packet on its way
 - Node process (local) and fast



11

Our Plan


- **Forwarding** this time
 - What routers do with packets
- **Routing** next time
 - Logically this comes first
 - But ignore it for now

12

Network Services (§5.1)



- What kind of service does the Network layer provide to the Transport layer?
 - How is it implemented at routers?

Service? What's he talking about?



13

Two Network Service Models

- Datagrams, or connectionless service
 - Like postal letters
 - (This one is IP) 
- Virtual circuits, or connection-oriented service
 - Like a telephone call 

14


Store-and-Forward Packet Switching

- Both models are implemented with store-and-forward packet switching
 - Routers receive a complete packet, storing it temporarily if necessary before forwarding it onwards
 - We use statistical multiplexing to share link bandwidth over time

15

Store-and-Forward (2)


- Switching element has internal buffering for contention



16

Store-and-Forward (3)


- Simplified view with per-port output buffering
 - Buffer is typically a FIFO (First In First Out) queue
 - If full, packets are discarded (congestion, later)



17

Datagram Model


- Packets contain a destination address; each router uses it to forward each packet, possibly on different paths



18

Datagram Model (2)


- Each router has a forwarding table keyed by address
 - Gives next hop for each destination address; may change



19

IP (Internet Protocol)

- Network layer of the Internet, uses datagrams (next)
 - IPv4 carries 32 bit addresses on each packet (often 1.5 KB)



20


Virtual Circuit Model

- Three phases:
 - Connection establishment, circuit is set up
 - Path is chosen, circuit information stored in routers
 - Data transfer, circuit is used
 - Packets are forwarded along the path
 - Connection teardown, circuit is deleted
 - Circuit information is removed from routers
- Just like a telephone circuit, but virtual in the sense that no bandwidth need be reserved; statistical sharing of links

21

Virtual Circuits (2)


- Packets only contain a short label to identify the circuit
 - Labels don't have any global meaning, only unique for a link



22

Virtual Circuits (3)


- Each router has a forwarding table keyed by circuit
 - Gives output line and next label to place on packet



23

Virtual Circuits (4)


- Each router has a forwarding table keyed by circuit
 - Gives output line and next label to place on packet



24

MPLS (Multi-Protocol Label Switching, §5.6.5)

- A virtual-circuit like technology widely used by ISPs
 - ISP sets up circuits inside their backbone ahead of time
 - ISP adds MPLS label to IP packet at ingress, undoes at egress



25

Datagrams vs Virtual Circuits


- Complementary strengths

Issue	Datagrams	Virtual Circuits
Setup phase	Not needed	Required
Router state	Per destination	Per connection
Addresses	Packet carries full address	Packet carries short label
Routing	Per packet	Per circuit
Failures	Easier to mask	Difficult to mask
Quality of service	Difficult to add	Easier to add

26

Internetworking (§5.5, 5.6.1)

- How do we connect different networks together?
 - This is called internetworking
 - We'll look at how IP does it



27


How Networks May Differ

- Basically, in a lot of ways:
 - Service model (datagrams, VCs)
 - Addressing (what kind)
 - QOS (priorities, no priorities)
 - Packet sizes
 - Security (whether encrypted)
- Internetworking hides the differences with a common protocol. (Uh oh.)

28

Connecting Datagram and VC networks

- An example to show that it's not so easy
 - Need to map destination address to a VC and vice-versa
 - A bit of a "road bump", e.g., might have to set up a VC



29

Internetworking – Cerf and Kahn

- Pioneered by Cerf and Kahn, the "fathers of the Internet"
 - In 1974, later led to TCP/IP
- Tackled the problems of interconnecting networks
 - Instead of mandating a single network technology




© 2009 IEEE

© 2009 IEEE

30

Internet Reference Model

- IP is the “narrow waist” of the Internet
 - Supports many different links below and apps above



31


IP as a Lowest Common Denominator

- Suppose only some networks support QoS or security etc.
 - Difficult for internetwork to support
- Pushes IP to be a “lowest common denominator” protocol
 - Asks little of lower-layer networks
 - Gives little as a higher layer service

32

IPv4 (Internet Protocol)


- Various fields to meet straightforward needs
 - Version, Header (IHL) and Total length, Protocol, and Header Checksum



33

IPv4 (2)


- Network layer of the Internet, uses datagrams
 - Provides a layer of addressing above link addresses (next)



34

IPv4 (3)


- Some fields to handle packet size differences (later)
 - Identification, Fragment offset, Fragment control bits



35

IPv4 (4)


- Other fields to meet other needs (later, later)
 - Differentiated Services, Time to live (TTL)



36

IP Prefixes (§5.6.1-5.6.2)


- What do IP addresses look like?
 - And IP prefixes, or blocks of addresses
 - (This is IPv4; we'll cover IPv6 later.)



37

IP Addresses


- IPv4 uses 32-bit addresses
 - Later we'll see IPv6, which uses 128-bit addresses
- Written in "dotted quad" notation
 - Four 8-bit numbers separated by dots



38

IP Prefixes – Modern


- Addresses are allocated in blocks called prefixes
 - Addresses in an L-bit prefix have the same top L bits
 - There are 2^{32-L} addresses aligned on 2^{32-L} boundary



39

IP Prefixes (2)


- Written in "IP address/length" notation
 - Address is lowest address in the prefix, length is prefix bits
 - E.g., 128.13.0.0/16 is 128.13.0.0 to 128.13.255.255
 - So a /24 ("slash 24") is 256 addresses, and a /32 is one address



40

IP Prefixes (3)


- More specific prefix
 - Has longer prefix, hence a smaller number of IP addresses
- Less specific prefix
 - Has shorter prefix, hence a larger number of IP addresses



41

IP Address Classes – Historical

- Originally, IP addresses came in fixed size blocks with the class/size encoded in the high-order bits
 - They still do, but the classes are now ignored



42


Public / Private IP Addresses

- Public IP addresses, e.g., 18.31.0.1
 - Valid destination on the global Internet
 - Must be allocated to you before use
 - Now exhausted ... time for IPv6!
- Private IP addresses
 - Can be used freely within private networks (home, small company)
 - 10.0.0.0/8, 172.16.0.0/12, 192.168.0.0/16
 - Need public IP address(es) and NAT to connect to global Internet

43

Allocating Public IP Addresses

- Follows a hierarchical process
 - Internet Assigned Numbers Authority (IANA) delegates to regional bodies (RIRs)
 - RIRs delegate to companies in their region
 - Companies assign to their customers/computers (later, DHCP)



44

IP Forwarding (§5.6.1-5.6.2)

- How do routers forward packets?
 - We'll look at how IP does it
 - (We'll cover routing later)



45


Recap

- We want the network layer to:
 - Scale to large networks
 - Using addresses with hierarchy } This lecture
 - Support diverse technologies
 - Internetworking with IP } More later
 - Use link bandwidth well
 - Lowest-cost routing } Next time

46

IP Forwarding

- IP addresses on one network belong to the same prefix
- Node uses a table that lists the next hop for IP prefixes




47

Longest Matching Prefix

- Prefixes in the table might overlap!
 - Combines hierarchy with flexibility
- Longest matching prefix forwarding rule:
 - For each packet, find the longest prefix that contains the destination address, i.e., the most specific entry
 - Forward the packet to the next hop router for that prefix

48


Longest Matching Prefix (2)



49

Host/Router Distinction

- In the Internet:
 - Routers do the routing, know which way to all destinations
 - Hosts send remote traffic (out of prefix) to nearest router



50

Host Forwarding Table

- Give using longest matching prefix
 - 0.0.0.0/0 is a default route that catches all IP addresses

Prefix	Next Hop
My network prefix	Send direct to that IP
0.0.0.0/0	Send to my router

51

Flexibility of Longest Matching Prefix

- Can provide default behavior, with less specific prefixes
 - To send traffic going outside an organization to a border router
- Can provide special case behavior, with more specific prefixes
 - For performance, economics, security, ...

52


Performance of Longest Matching Prefix

- Uses hierarchy for a compact table
 - Benefits from less specific prefixes
- Finding longest match more complex than table lookup
 - Was a concern for fast routers, but not an issue in practice these days

53

Other Aspects of Forwarding

- It's not all about addresses ...



54

Other Aspects (2)

- Decrement TTL value
 - Protects against loops
- Checks header checksum
 - To add reliability
- Fragment large packets
 - Split to fit it on next link
- Send congestion signals
 - Warns hosts of congestion
- Generates error messages
 - To help manage network
- Handle various options

} Coming later

55

Helping IP with ARP, DHCP (§5.6.4)

- Filling in the gaps we need to make IP forwarding work in practice
 - Getting IP addresses (DHCP)
 - Mapping IP to link addresses (ARP)

56

Getting IP Addresses

- Problem:
 - A node wakes up for the first time ...
 - What is its IP address? What's the IP address of its router? Etc.
 - At least Ethernet address is on NIC

57

Getting IP Addresses (2)

1. Manual configuration (old days)
 - Can't be factory set, depends on use
2. A protocol for automatically configuring addresses (DHCP)
 - Shifts burden from users to IT folks

58

DHCP

- DHCP (Dynamic Host Configuration Protocol), from 1993, widely used
- It leases IP address to nodes
- Provides other parameters too
 - Network prefix
 - Address of local router
 - DNS server, time server, etc.

59

DHCP Protocol Stack

- DHCP is a client-server application
 - Uses UDP ports 67, 68


DHCP
UDP
IP
Ethernet

60

DHCP Addressing

- Bootstrap issue:
 - How does node send a message to DHCP server before it is configured?
- Answer:
 - Node sends broadcast messages that delivered to all nodes on the network
 - Broadcast address is all 1s
 - IP (32 bit): 255.255.255.255
 - Ethernet (48 bit): ff:ff:ff:ff:ff:ff

61



DHCP Messages (2)

- To renew an existing lease, an abbreviated sequence is used:
 - REQUEST, followed by ACK
- Protocol also supports replicated servers for reliability

63

Sending an IP Packet

- Problem:
 - A node needs Link layer addresses to send a frame over the local link
 - How does it get the destination link address from a destination IP address?

64

ARP (Address Resolution Protocol)

- Node uses it to map a local IP address to its Link layer addresses

```

graph TD
    subgraph Link_layer [Link layer]
        S_Ethernet[Source Ethernet]
        D_Ethernet[Dest. Ethernet]
    end
    subgraph IP_layer [IP layer]
        S_IP[Source IP]
        D_IP[Dest. IP]
    end
    Payload[Payload ...]
    
    S_Ethernet --- IP_layer
    D_Ethernet --- IP_layer
    
    From_NIC[From NIC] --> S_Ethernet
    From_ARP[From ARP] --> D_Ethernet
    From_DHCP[From DHCP] --> S_IP
    
```

65



ARP Protocol Stack

- ARP sits right on top of link layer
 - No servers, just asks node with target IP to identify itself
 - Uses broadcast to reach all nodes

```

graph TD
    ARP[ARP] --- Ethernet[Ethernet]
    
```

66



- ### Discovery Protocols
- Help nodes find each other
 - There are more of them!
 - E.g., zeroconf, Bonjour
 - Often involve broadcast
 - Since nodes aren't introduced
 - Very handy glue
- 69

- ### Packet Fragmentation (§5.5.5)
- How do we connect networks with different maximum packet sizes?
 - Need to split up packets, or discover the largest size to use
-
- 70

- ### Packet Size Problem
- Different networks have different maximum packet sizes or MTUs
 - MTU = Maximum Transmission Unit
 - E.g., Ethernet 1.5K, WiFi 2.3K
 - Prefer large packets for efficiency
 - But what size is too large?
 - Difficult because node does not know complete network path
- 71

- ### Packet Size Solutions
- Fragmentation (now)
 - Split up large packets in the network if they are too big to send
 - Classic method, but dated
 - Discovery (next)
 - Find the largest packet that fits on the network path and use it
 - IP uses today instead of fragmentation
- 72

IPv4 Fragmentation

- Routers fragment packets that are too large to forward
- Receiving host reassembles to reduce load on routers

73

IPv4 Fragmentation Fields

- Header fields used to handle packet size differences
 - Identification, Fragment offset, MF/DF control bits

74

IPv4 Fragmentation Procedure

- Routers split a packet that is too large:
 - Typically break into large pieces
 - Copy IP header to pieces
 - Adjust length on pieces
 - Set offset to indicate position
 - Set MF (More Fragments) on all pieces except last
- Receiving hosts reassembles pieces:
 - Identification field links pieces together, MF tells receiver when it has all pieces

75

IPv4 Fragmentation (2)

Before
MTU = 2300

ID = 0x12ef
Data Len = 2300
Offset = 0
MF = 0

After
MTU = 1500

(Ignore length of headers)

ID =
Data Len =
Offset =
MF =

ID =
Data Len =
Offset =
MF =

76

IPv4 Fragmentation (3)

Before
MTU = 2300

ID = 0x12ef
Data Len = 2300
Offset = 0
MF = 0

After
MTU = 1500

ID = 0x12ef
Data Len = 1500
Offset = 0
MF = 1

ID = 0x12ef
Data Len = 800
Offset = 1500
MF = 0

77

IPv4 Fragmentation (4)

- It works!
 - Allows repeated fragmentation!
- But fragmentation is undesirable
 - More work for routers, hosts
 - Magnifies severity of packet loss
 - Security vulnerabilities too

78

Path MTU Discovery

- Discover the MTU that will fit
 - So we can avoid fragmentation
 - The method in use today
- Host tests path with large packet
 - Routers provide feedback if too large; they tell host what size would have fit


79

Path MTU Discovery (2)



80

Path MTU Discovery (3)



81


Path MTU Discovery (4)

- Process may seem involved
 - But usually quick to find right size
- Path MTU depends on the path, so can change over time
 - Search is ongoing
- Implemented with ICMP (next)
 - Set DF (Don't Fragment) bit in IP header to get feedback messages

82

Error Handling with ICMP (§5.6.4)

- What happens when something goes wrong during forwarding?
 - Need to be able to find the problem



83


Internet Control Message Protocol

- ICMP is a companion protocol to IP
 - They are implemented together
 - Sits on top of IP (IP Protocol=1)
- Provides error report and testing
 - Error is at router while forwarding
 - Also testing that hosts can use

84

ICMP Errors

- When router encounters an error while forwarding:
 - It sends an ICMP error report back to the IP source address
 - It discards the problematic packet; host needs to rectify



85


ICMP Message Format

- Each ICMP message has a Type, Code, and Checksum
- Often carry the start of the offending packet as payload
- Each message is carried in an IP packet

86

ICMP Message Format (2)

- Each ICMP message has a Type, Code, and Checksum
- Often carry the start of the offending packet as payload
- Each message is carried in an IP packet



87

Example ICMP Messages


Name	Type / Code	Usage
Dest. Unreachable (Net or Host)	3 / 0 or 1	Lack of connectivity
Dest. Unreachable (Fragment)	3 / 4	Path MTU Discovery
Time Exceeded (Transit)	11 / 0	Traceroute
Echo Request or Reply	8 or 0 / 0	Ping

Testing, not a forwarding error: Host sends Echo Request, and destination responds with an Echo Reply

88

Traceroute


- IP header contains TTL (Time to live) field
 - Decremented every router hop, with ICMP error if it hits zero
 - Protects against forwarding loops



89

Traceroute (2)

- Traceroute repurposes TTL and ICMP functionality
 - Sends probe packets increasing TTL starting from 1
 - ICMP errors identify routers on the path



90

IP Version 6 (§5.6.3)

- IP version 6, the future of IPv4 that is now (still) being deployed

91

Internet Growth

- At least 1.1 billion Internet hosts and likely to grow further with IoT and mobile devices
- And we're using 32-bit addresses!

Source: Internet Systems Consortium (www.isc.org)

92

The End of New IPv4 Addresses

- Now running on leftover blocks held by the regional registries; much tighter allocation policies

Exhausted on 4/11 and 9/12!

IANA (All IPs)

Exhausted on 2/11!

End of the world ? 12/21/12?

93

IP Version 6 to the Rescue

- Effort started by the IETF in 1994
 - Much larger addresses (128 bits)
 - Many sundry improvements
- Became an IETF standard in 1998
 - Nothing much happened for a decade
 - Hampered by deployment issues, and a lack of adoption incentives
 - Big push ~2011 as exhaustion looms

94

IPv6 Deployment

Percentage of users accessing Google via IPv6

Time for growth!

Source: Google IPv6 Statistics, 30/1/13

95

IPv6


- Features large addresses
 - 128 bits, most of header
- New notation
 - 8 groups of 4 hex digits (16 bits)
 - Omit leading zeros, groups of zeros

Ex: 2001:0db8:0000:0000:0000:ff00:0042:8329
→

96

IPv6 (2)

- Lots of other, smaller changes
 - Streamlined header processing
 - Flow label to group of packets
 - Better fit with “advanced” features (mobility, multicasting, security)



97


IPv6 Transition

- The Big Problem:
 - How to deploy IPv6?
 - Fundamentally incompatible with IPv4
- Dozens of approaches proposed
 - Dual stack (speak IPv4 and IPv6)
 - Translators (convert packets)
 - Tunnels (carry IPv6 over IPv4)

98

Tunneling


- Native IPv6 islands connected via IPv4
 - Tunnel carries IPv6 packets across IPv4 network



99

Tunneling (2)

- Tunnel acts as a single link across IPv4 network
 - Difficulty is to set up tunnel endpoints and routing



100

Network Address Translation (§5.6.2)


- What is NAT (Network Address Translation)? How does it work?
 - NAT is widely used at the edges of the network, e.g., homes



101

Layering Review

- Remember how layering is meant to work?
 - “Routers don’t look beyond the IP header.” Well ...



102

Middleboxes

- Sit “inside the network” but perform “more than IP” processing on packets to add new functionality
 - NAT box, Firewall / Intrusion Detection System

103

Middleboxes (2)

- Advantages
 - A possible rapid deployment path when there is no other option
 - Control over many hosts
- Disadvantages
 - Breaking layering interferes with connectivity; strange side effects
 - Poor vantage point for many tasks

104

NAT (Network Address Translation) Box

- NAT box connects an internal network to an external network
 - Many internal hosts are connected using few external addresses
 - Middlebox that “translates addresses”
- Motivated by IP address scarcity
 - Controversial at first, now accepted

105

NAT (2)

- Common scenario:
 - Home computers use “private” IP addresses
 - NAT (in AP/firewall) connects home to ISP using a single external IP address

106

How NAT Works

- Keeps an internal/external table
 - Typically uses IP address + TCP port
 - This is address and port translation

What host thinks	What ISP thinks
Internal IP:port	External IP : port
192.168.1.12 : 5523	44.25.80.3 : 1500
192.168.1.13 : 1234	44.25.80.3 : 1501
192.168.2.20 : 1234	44.25.80.3 : 1502

- Need ports to make mapping 1-1 since there are fewer external IPs

107

How NAT Works (2)


- Internal → External:
 - Look up and rewrite Source IP/port

108

How NAT Works (3)

- External → Internal

- Look up and rewrite Destination IP/port




109

How NAT Works (4)

- Need to enter **new translations** in the table for it to work

- Create external name when host makes a TCP connection



110

NAT Downsides

- Connectivity has been broken!
 - Can only send incoming packets after an outgoing connection is set up
 - Difficult to run servers or peer-to-peer apps (Skype) at home
- Doesn't work so well when there are no connections (UDP apps)
- Breaks apps that unwisely expose their IP addresses (FTP)

111

NAT Upsides

- Relieves much IP address pressure
 - Many home hosts behind NATs
- Easy to deploy
 - Rapidly, and by you alone
- Useful functionality
 - Firewall, helps with privacy
- Kinks will get worked out eventually
 - "NAT Traversal" for incoming traffic

112